

IN THE CLAIMS

Please amend the claims as follows:

1. (Previously Presented) A method for providing a composite objective image quality metric of a set of a plurality of random video features, said method comprising the steps of:

- (a) receiving a video sequence for image quality
5 evaluation;
- (b) providing an objective metric image quality controller comprising a random set of metrics ranging from M_1 to M_n without cross correlation information;
- (c) applying said each one metric of said set of metrics
10 individually to said video sequence so that said each one metric of said random set of metrics provides an individual objective scoring value of said video sequence ranging from x_1 to x_n ;
- (d) determining a plurality of sets of weights (w_1 to w_n) which correlate to predetermined subjective evaluations of image
15 quality for a predetermined plurality of video sequences (n), each one set of weights of said plurality of sets of weights being assigned a range having an incremental value equal to said range divided by a number of combinations for said each one set of weights;

20 (e) weighting by said each one set of weights each individual objective scoring value x_1 to x_n provided by said each one metric of said random set of metrics in step (c);

(f) adding the weighted individual objective scoring values of said random set of metrics into a single objective

25 evaluation F, wherein each weighted individual scoring value from step (e) is multiplied by each individual objective scoring value x_1 to x_n from step (c);

(g) calculating a correlation factor R to provide a correlation value for the objective evaluation F and the plurality

30 of video sequences (n);

(h) repeating steps (e), (f) and (g) for each set of weights provided in step (d) to determine a plurality of correlation factors R;

(i) ranking said plurality of correlation factors R,

35 wherein a particular correlation factor of said plurality of correlation factors having a particular correlation value closest to 1 represents a best ranking of the respective combined metrics in step (e) for each set of weights; and

(j) providing image quality information to at least one

40 of a system optimizer and the video processing module as to the best ranking of the respective combined metrics obtained in step (i) to provide a best perceptual image quality.

2. (Original) The method according to Claim 1, where the combining recited in step (f) is performed non-linearly by a quadratic model to obtain the objective evaluation F.

3. (Currently Amended) The method according to Claim 2, wherein when a number of the set of metrics =4, then the quadratic model to obtain the objective evaluation F is:

$$F = w_1x_1^2 + w_2x_2^2 + w_3x_3^2 + w_4x_4^2 + w_5x_1x_2 + w_6x_1x_3 + w_7x_1x_4 + w_8x_2x_3 + w_9x_2x_4 + w_{10}x_3x_4.$$

4. (Original) The method according to Claim 2, wherein when a number of the sets of metrics=n, then the quadratic model to obtain the objective evaluation F is:

$$F = \left(\sum_{i=1}^n w_i x_i \right)^2, \text{ wherein "n" is a non-zero value.}$$

5. (Currently Amended) The method according to Claim 1, wherein a number of sets of metrics=n, and step (f) includes using a polynomial degree for non-linear combination to an Lth order, and said objective evaluation F is obtained according to:

$$F = \left(\sum_{i=1}^n w_i x_i \right)^L, \text{ wherein "n" is a non-zero value.}$$

6. (Original) The method according to Claim 1, wherein the calculating of the correlation factor R in step (g) is performed by using a Spearman rank order comprising the following equation:

$$R=1-\frac{6*(X-Y)'(X-Y)}{k(k^2-1)},$$

5 wherein X is equal to a vector of ranked k objective values for the k sequences (k * 1), and Y is equal to a vector of ranked k subjective evaluation for the k sequences (k * 1).

7. (Original) The method according to Claim 2, wherein the calculating of the correlation factor R in step (g) is performed by using a Spearman rank order comprising the following equation:

$$R=1-\frac{6*(X-Y)'(X-Y)}{k(k^2-1)},$$

5 wherein X is equal to a vector of ranked k objective values for the k sequences (k * 1), and Y is equal to a vector of ranked k subjective evaluation for the k sequences (k * 1).

8. (Original) The method according to Claim 4, wherein the calculating of the correlation factor R in step (g) is performed by using a Spearman rank order comprising the following equation:

$$R=1-\frac{6*(X-Y)'(X-Y)}{k(k^2-1)},$$

5 wherein X is equal to a vector of ranked k objective values for the k sequences ($k * 1$), and Y is equal to a vector of ranked k subjective evaluation for the k sequences ($k * 1$).

9. (Currently Amended) The method according to Claim 1,
wherein said method further comprising comprises the step of:

 (k) selecting a best set of weights from the plurality of sets of weights provided in step (d), said best set of weights
5 being heuristically determined by a genetic algorithm that increases dynamically a size of the assigned range of said each one set of weights provided in step (d).

10. (Currently Amended) The method according to Claim 1,
wherein said method further comprising comprises the step of:

 (k) selecting a best set of weights from the plurality of sets of weights provided in step (d), said best set of weights
5 being heuristically determined by a genetic algorithm that that enables finding the best solution that maximizes the correlation factor R of the overall objective image quality F with the subjective evaluation without performing an exhaustive search to find the best set of weights.

11. (Currently Amended) The method according to Claim 2,
wherein said method further comprising comprises the step of:

(k) selecting a best set of weights from the plurality of sets of weights provided in step (d), said best set of weights
5 being heuristically determined by a genetic algorithm that increases dynamically a size of the assigned range of said each one set of weights provided in step (d).

12. (Currently Amended) The method according to Claim 2,
wherein said method further comprising comprises the step of:

(k) selecting a best set of weights from the plurality of sets of weights provided in step (d), said best set of weights
5 being heuristically determined by a genetic algorithm that enables finding the best solution that maximizes the correlation factor R of the overall objective image quality F with the subjective evaluation without performing an exhaustive search to find the best set of weights.

13. (Currently Amended) The method according to Claim 7,
wherein said method further comprising comprises the step of:

(k) selecting a best set of weights from the plurality of sets of weights provided in step (d), said best set of weights
5 being heuristically determined by a genetic algorithm that increases dynamically a size of the assigned range of said each one set of weights provided in step (d).

14. (Currently Amended) The method according to Claim 7,
wherein said method further comprising comprises the step of:

(k) selecting a best set of weights from the plurality of
sets of weights provided in step (d), said best set of weights
5 being heuristically determined by a genetic algorithm that that
enables finding the best solution that maximizes the correlation
factor R of the overall objective image quality F with the
subjective evaluation without performing an exhaustive search to
find the best set of weights.

15. (Original) The method according to Claim 9, wherein said
genetic algorithm comprises a chromosome having a number of genes
corresponding to quantity of said plurality of sets of weights in
step (d), and each gene of said number of genes being represented
5 by a quantity of bits sufficient to represent all possible tested
values for said each one weight in binary, wherein all possible
tested values being equal to an absolute value of the assigned
range for said each one set of weights provided in step (d) divided
by the incremental value for said each one set of weights.

16. (Original) The method according to Claim 15, wherein said
genetic algorithm alters a bit pattern of said chromosome by at
least one of mutation and crossover while minimizing a deviation in

the correlation factor R, so that a best solution comprises a
5 deviation closest to zero.

17. (Original) The method according to Claim 10, wherein said genetic algorithm comprises a chromosome having a number of genes corresponding to quantity of said plurality of sets of weights in step (d), and each gene of said number of genes being represented
5 by a quantity of bits sufficient to represent all possible tested values for said each one weight in binary, wherein all possible tested values being equal to a value of the assigned range for said each one set of weights provided in step (d) divided by the incremental value for said each one set of weights.

18. (Original) The method according to Claim 17, wherein said genetic algorithm alters a bit pattern of said chromosome by at least one of mutation and crossover while minimizing a deviation in the correlation factor R, so that a best solution comprises a
5 deviation closest to zero.

19. (Original) The method according to Claim 17, wherein said genetic algorithm alters a bit pattern of said chromosome by at least one of mutation and crossover while minimizing a deviation in the correlation factor R, so that a best solution comprises one of
5 1) the deviation within a predetermined percentage of a

predetermined value, and 2) the deviation can not be decreased any further after a certain predetermined number of attempts.

20. (Original) The method according to Claim 11, wherein said genetic algorithm comprises a chromosome having a number of genes corresponding to quantity of said plurality of sets of weights in step (d), and each gene of said number of genes being represented
5 by a quantity of bits sufficient to represent all possible tested values for said each one weight in binary, wherein all possible tested values being equal to a value of the assigned range for said each one set of weights provided in step (d) divided by the incremental value for said each one set of weights.

21. (Original) The method according to Claim 20, wherein said genetic algorithm alters a bit pattern of said chromosome by at least one of mutation and crossover while minimizing a deviation in the correlation factor R , so that a best solution comprises a
5 deviation closest to zero.

22. (Original) The method according to Claim 12, wherein said genetic algorithm comprises a chromosome having a number of genes corresponding to quantity of said plurality of sets of weights in step (d), and each gene of said number of genes being represented
5 by a quantity of bits sufficient to represent all possible tested

values for said each one weight in binary, wherein all possible tested values being equal to a value of the assigned range for said each one set of weights provided in step (d) divided by the incremental value for said each one set of weights.

23. (Original) The method according to Claim 22, wherein said genetic algorithm alters a bit pattern of said chromosome by at least one of mutation and crossover while minimizing a deviation in the correlation factor R, so that a best solution comprises a
5 deviation closest to zero.

24. (Original) The method according to Claim 13, wherein said genetic algorithm comprises a chromosome having a number of genes corresponding to quantity of said plurality of sets of weights in step (d), and each gene of said number of genes being represented
5 by a quantity of bits sufficient to represent all possible tested values for said each one weight in binary, wherein all possible tested values being equal to a value of the assigned range for said each one set of weights provided in step (d) divided by the incremental value for said each one set of weights.

25. (Original) The method according to Claim 24, wherein said genetic algorithm alters a bit pattern of said chromosome by at least one of mutation and crossover while minimizing a deviation in

the correlation factor R , wherein the deviation = $1-R$, and a best
5 solution determined by said algorithm comprises a deviation closest
to zero.

26. (Original) The method according to Claim 13, wherein said
genetic algorithm comprises a chromosome having a number of genes
corresponding to quantity of said plurality of sets of weights in
step (d), and each gene of said number of genes being represented
5 by a quantity of bits sufficient to represent all possible tested
values for said each one weight in binary, wherein all possible
tested values being equal to a value of the assigned range for said
each one set of weights provided in step (d) divided by the
incremental value for said each one set of weights, and
10 wherein said genetic algorithm alters a bit pattern of said
chromosome by at least one of mutation and crossover while
minimizing a deviation in the correlation factor R , wherein the
deviation = $1-R$, and a best solution determined by said algorithm
comprises a deviation closest to a predetermined value.

27. (Original) The method according to Claim 26, wherein said
predetermined value comprises a value that cannot be reduced by
further search.

28. (Original) The method according to Claim 24, wherein said genetic algorithm alters a bit pattern of said chromosome by at least one of mutation and crossover while minimizing a deviation in the correlation factor R, wherein the deviation = 1-R, and a best
5 solution determined by said algorithm comprises a deviation closest to a predetermined value.

29. (Currently Amended) A system for providing a composite image of a random set of video features, comprising:
means for receiving a video sequence;
an objective metric image quality controller comprising a
5 plurality of objective metrics without prior dependency information thereof~~and~~, means for selecting a metric from said plurality of objective metrics for evaluating image quality of the video sequence, and means for applying each of said plurality of objective metrics by said objective metric image quality controller
10 to said video sequence and individually scoring said video sequence from x_1 to x_n ;
means for determining a plurality of sets of weights (w_1 to w_n) by said objective metric image quality controller, said plurality of sets of weights correlate to predetermined subjective
15 evaluations of image quality for a predetermined plurality of video sequences (n), each one set of weights being assigned a range having an incremental value equal to a value of said range divided

by a number of combinations for said each one set of weights, which includes means for weighting by said each one set of weights each individual objective scoring value x_1 to x_n provided by said each one metric of ~~said a~~ a random set of metrics;

means for combining metrics of the weighted individual objective scoring values of ~~a~~ a random set of metrics corresponding to the random set of video features into a single objective evaluation F , wherein each weighted individual scoring value is multiplied by a corresponding weight; and

means for calculating a plurality of correlation factors R to provide a correlation value for the objective evaluation F and the plurality of video sequences (n), which includes means for ranking said plurality of correlation factors R , wherein a particular correlation factor of said plurality of correlation factors having a particular correlation value closest to 1 represents a best ranked respective combined metrics for each set of weights; —

wherein the best ranked respective combined metrics determined by said objective metric image quality controller is used to provide a best objective perceptual quality of said video sequence.

30. (Original) The system according to Claim 29, wherein said means for combining metrics includes means for non-linear

combination by a quadratic model to obtain the objective evaluation F.

31. (Currently Amended) The system according to Claim 29, wherein said means for combining metrics includes means for non-linear combination by a polynomial degree to an Lth order, and a number of sets of metrics=n, to obtain the objective evaluation F
5 according to:

$$F = \left(\sum_{i=1}^n w_i x_i \right)^2 - \underline{\quad}, \text{ wherein " n " is a non-zero value.}$$

32. (Original) The system according to Claim 30, wherein said means for calculating the plurality of correlation factors R includes using a Spearman rank order comprising:

$$R = 1 - \frac{6 * (X - Y)'(X - Y)}{k(k^2 - 1)},$$

5 wherein X is equal to a vector of ranked k objective values for the k sequences (k * 1), and Y is equal to a vector of ranked k subjective evaluation for the k sequences (k * 1).

33. (Original) The system according to Claim 32, wherein said means for determining includes means for selecting a best set of weights from the plurality of sets of weights, said best set of

weights being heuristically determined by a genetic algorithm
5 module that increases dynamically a size of the assigned range of
said each one set of weights.

34. (Original) The system according to Claim 33, wherein said
means for determining includes means for selecting a best set of
weights from the plurality of sets of weights, said best set of
weights being heuristically determined by a genetic algorithm
5 module that enables finding the best solution that maximizes the
correlation factor R of the overall objective image quality F with
the subjective evaluation without performing an exhaustive search
to find the best set of weights.